

44415
46415
09-14 DODGE
CHALLENGER



44415
46415
09-14 DODGE
CHALLENGER

09-14 DODGE CHALLENGER

Sport Series Grille

TOOLS REQUIRED

8mm Socket and Ratchet

PARTS LIST

- (6) 2" Flange Brackets
- (6) 2 3/4" Threaded "J" Hooks
- (10) 6/32 Nylon Lock Nuts
- (4) Large Black Washers
- (2) Logo Plates w/ Adhesive Backing
- (1) Sport Series Grille

Step 1

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION. Remove the factory logos from the factory grille shell. They are held on by plastic clips. Reach behind the factory grille and squeeze the clips together and pull the logo forward.

Step 2

If you would like to reinstall the logos on the mesh grille, cut the plastic tabs off of the back of the logos and sand them with sandpaper or a file so the back is flat. Peel the backing off of the adhesive and press it onto the back of the factory logos. Firmly press the logos onto the supplied logo plates. Install the logos onto the mesh grille before installing the mesh grille on the vehicle. Use a washer and 6/32 nylon lock nut on the back of the logo plates to secure them to the mesh grille.

Step 3

Insert the grille into the opening in the factory grille.

Step 4

The 6 threaded "J" hooks will be inserted through the mesh and hook onto the mesh. (Fig 1) They install onto the 4 corners of the grille and in the center at the top and bottom of the grille. The threaded ends will go through the black plastic of the factory grille.

Step 5

Reach down between the radiator cover and factory grille then take the small tapered brackets and slide them onto the threaded hook ends. Install a 6/32" nylon lock nut onto the threaded ends and tighten with an 8mm socket and ratchet. (Fig 2) Repeat this on all 6 threaded hooks. Installation is now complete.

