

7715721
2013-2014
FORD F-150



7715721-BR
2013-2014
FORD F-150

2013-2014 FORD F-150 Except Platinum

LASER X Grille

TOOLS REQUIRED:

Plastic Prybar
Die Grinder
Drill & 1/8 Drillbit

PARTS LIST:

(1) Mesh Grille (2) Flat nuts
(8) L-Brackets
(8) 6/32 Nylon Lock Nuts
(2) #8 Screws

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION.

Step 1 Remove Factory Grille Shell

- Remove 6 Bolts along the top of the Grille Shell. (Fig. 1)
- Remove 2 Clips along the Vehicle Support Bar. (Fig. 2)
- Place the Plastic Prybar in between the Grille Shell and Hood, Firmly start nudging away the Grille Shell from the Hood. (the Grille Shell is latched on with Clips.). (Fig. 3) Remove the Grille Shell.

Step 2 Installing Grille

- With a Die Grinder, Remove the Vertical and Horizontal Plastic Bars that are around the Grille. (Fig. 4 & 5)
- Place the Grille into the Grille Opening. (Fig. 6)
- Place L-Brackets onto the Threaded Studs that are on the Grille and use Nylon Lock Nuts. (Fig. 7)
- Use the 1/8 Drillbit to Drill through the Brackets that are on the Sides of the Grille and place #8 Screws through them, Place Flatnuts behind to Thread the #8 Screw. (Fig. 8)

INSTALLATION COMPLETE

