

54525
51525
2013 FORD
MUSTANG GT



54525
51525
2013 FORD
MUSTANG GT

2013 FORD MUSTANG GT

Mesh Grille

Install time: 30 Mins.

TOOLS REQUIRED:

Screwdriver
Socketwrench
Flat Screwdriver

PARTS LIST:

(1) Mesh Grille
(4) #8 6hd 2" Screws
(4) U-Nuts
(4) Flange Brackets w/Center Hole

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS
BEFORE ATTEMPTING INSTALLATION.

Step 1 Factory Removal

- Remove 7 Pop Clips from the Plastic Cover. (Fig. 1)
- Remove Plastic Cover
- Insert the U-Nut through the Flange Bracket (Have the wider hole on the U-Nut face towards you). (Fig. 2)

Step 2 Mustang Logo Removal

- From behind the grille carefully remove the Mustang logo and place it on the Mesh Grille with provided Nylon Lock Nuts.

Step 3 Grille Installation

- Place Mesh Grille onto the Factory Grille. (Fig. 3)
- Insert the Screws onto the Brackets that are on the Mesh Grille. (Fig. 4)
- From Behind the Factory Grille, Place the Flange Bracket through the Screws and Thread in. (Flange bracket hooks must face the Grille so it latches.) (Fig. 5)
Repeat for Remaining Screws.

INSTALLATION COMPLETE

