

**55519**  
**10-12 FORD**  
**MUSTANG GT**



**55519**  
**10-12 FORD**  
**MUSTANG GT**

## **10-12 FORD MUSTANG** **Upper Class Bumper Grille GT Models**

### **TOOLS REQUIRED:**

Socket and Ratchet Set  
Flat/Phillips Screwdrivers

### **PARTS LIST:**

(4) 2" Flange Brackets  
(4) 6/32" Nylon Lock Nuts  
(1) Upper Class Bumper Grille

### **PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE**

**INSTALLATION.** Auto makers offer varied models to each vehicle and occasionally manufacture more than one body style of the same model. To assure your part is correct; our tech department can be contacted at [tech@trexbillet.com](mailto:tech@trexbillet.com) to verify fitment or assist with tech questions. All other inquires can be directed to [info@trexbillet.com](mailto:info@trexbillet.com). In the event you do not have internet access please call 1-800-287-5900.



### **Step 1 Top Radiator Cover Removal**

First you will remove the top radiator cover from the vehicle. There are 8 plastic pop clips on the radiator cover that need to be removed with a flat screwdriver by prying the head upward (Fig 1). Now you can remove the radiator cover. This will give you access to the rear of the factory bumper.

### **Step 2 Bumper Grille Installation**

With the radiator cover removed, place the bumper mesh grille into the factory bumper opening (Fig 2). Reach down through the top where the radiator cover was removed and place the four 2" Flange Brackets over the threaded studs on the backside of the bumper mesh grille, the bent ends will face forward. Install the four 6/32" nylon lock nuts over the 2" flange brackets and tighten (Fig 3). Reinstall the radiator cover. Installation complete.

