



ZROADZ

DYNAMIC LED MOUNTING SOLUTIONS



2010-2014 FORD SVT RAPTOR

Z325661 / Z325661-KIT FRONT BUMPER LED LIGHT MOUNTS

PARTS ARE PATENT PENDING. ALL RIGHTS RESERVED - COPYRIGHT ©2016 - ZROADZ LED, INC.

PARTS INCLUDED

ZROADZ BRACKETS

- (1) Driver Side Bracket Mount
- (1) Passenger Side Bracket Mount



LED LIGHTS INCLUDED

Z325661 - NO LED Lights are included

Z325661-KIT - (1) 20" ZROADZ LED Light Bar

HARDWARE INCLUDED

Z325651

- (2) - 1/4" Nuts
- (2) - 1/4" Lock Washers
- (2) - 1/4 x 1.5" Fender Washers

Z325651-KIT

- (2) - 1/4" Nuts
- (2) - 1/4" Lock Washers
- (2) - 1/4 x 1.5" Fender Washers
- (1) - Torx Bit T-40
- (2) - M8 Split Lock Washers
- (2) - M8 Tamper Proof Button Head Allen Cap
- Stainless Steel Bolts

TOOLS REQUIRED

- Various Socket Set
- Various Wrenches
- Ratchet Tool
- Ratchet Extensions

INSTALLATION GUIDE

START HERE

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE INSTALLATION. Auto makers offer varied models to each vehicle and occasionally manufacture more than one body style of the same model. To assure your part is correct; our tech department can be contacted at orders@zroadz.com to verify fitment and assist with technical questions. All other inquires can be directed to orders@zroadz.com. In the event you do not have internet access please call 844-653-8040.

* APPLICATION MODELS VARY. WE RECOMMEND TO VERIFY FITMENT BEFORE BEGINNING INSTALLATION
* IMAGES FEATURED IN THE INSTRUCTION DOCUMENTS MAY NOT ALWAYS EXACTLY MATCH YOUR GRILL.

BEFORE YOU BEGIN

START HERE: Turn off engine, chalk tires with stop block, open the hood and disconnect the battery.

LED LIGHT BRACKET INSTALLATION



FIG 1

STEP 1

SEE FIGURE 1 & 2

- 1) Layout your parts. Configure and assemble the mounts to the LED Light Bar as seen in Figure #1.

FIG 2



* LED LIGHTS INCLUDED IN #Z325661-KIT ONLY



ZROADZ

DYNAMIC LED MOUNTING SOLUTIONS



FIG 3

STEP 2

SEE FIGURES 3

2) Using the provided hardware, slip the M8 Split Lock Washer over the M8 Tamper Proof Button Head Allen Cap Stainless Steel Bolts and insert into the ZROADZ Bracket Mounting Hole.



FIG 4

STEP 3

SEE FIGURE 4

3) Line up the ZROADZ Bracket Mounting holes with the LED Light mount and use the Torq Bit T-40 to tighten the hardware.



FIG 5



FIG 6

STEP 4

SEE FIGURES 5 & 6

4) Remove the Ford Raptor's Lower Bumper Grille from the Lower Bumper Opening. Refer to Figures #5 & #6.



FIG 7



FIG 8



FIG 9

STEP 5

SEE FIGURES 7 - 10

5) Insert the fully assembled 20" LED Light Bar and ZROADZ Mounting Brackets into the Ford Raptor's Lower Bumper Opening as seen in Figures #7 - #10.



FIG 10

INSTALL PROCESS - CONTINUED



ZROADZ

DYNAMIC LED MOUNTING SOLUTIONS



FIG 11

STEP 6

SEE FIGURES 11 - 12

6) Prop up the assembled LED Light & Mounts so that the ZROADZ's Bracket Mounting Studs protrude through the pre-determined mounting holes.



FIG 12

STEP 7

SEE FIGURE 12 - 13

7) From behind the lower bumper, Slip over the 1/4 x 1.5" Fender Washers and 1/4 Lock Nuts over each ZROADZ Bracket Mounting Stud.



FIG 13

STEP 8

SEE FIGURE 14

8) Slip over the provided 1/4 nuts over each ZROADZ Bracket Mounting Stud.

STEP 9

SEE FIGURES 15 & 16

9) Tighten up the nuts so that the ZROADZ Bracket Mountins are now fully secure and locked into place.

STEP 10

ADJUSTMENT TIPS

6) To adjust the angle of your Light Bar, rotate the LED(s) to adjust the angles till your desired light pattern is reached. You may than tighten the hardware and also mounting bracket and secure everything into place. Be careful not to over tighten the mounting hardware.

It is best to adjust the angle with the vehicle on level ground with lights facing a wall, garage door or other solid barrier. We recommend checking from a distance of 25'. Your installation is now completed.



FIG 14



FIG 15



FIG 16



FIG 17

INSTALL PROCESS - COMPLETE



ZROADZ

DYNAMIC LED MOUNTING SOLUTIONS

ZROADZ PRODUCT WARRANTY

ZROADZ PRODUCT WARRANTY

ZROADZ warrants its grille products to be free from defects in material and workmanship for the lifetime of the grille. ZROADZ warrants the finish of its grille products for a 3 year period beginning at the time of sale to the end user. These warranties are limited warranties and do not cover abuse, modification or improper installation nor do they cover finish failure caused by caustic cleaning agents, road salts or other chemicals. ZROADZ reserves the right to repair or replace a defective product at its sole discretion. Any ZROADZ product must be returned to ZROADZ for warranty consideration and must be returned at the customer's expense. In the event that the product is deemed to be defective, the repaired or replaced item will be returned via a surface shipping method to the customer at ZROADZ expense. No provision is made for any labor, rental car or other costs incurred by the failure of its products.

LED LIGHTING EQUIPMENT INSTALLATION / DISCLAIMER

WARNING

PLEASE CONSULT YOUR LOCAL AUTOMOTIVE ELECTRICAL PROFESSIONAL FOR INSTALLATION SERVICES AND ADVICE. ZROADZ IS ONLY EQUIPPED TO PROVIDE BASIC TECHNICAL ASSISTANCE DUE TO THE DIVERSITY OF VEHICLES, VEHICLE OPTIONS & MODIFICATIONS AND LIGHTING CONFIGURATION OPTIONS AVAILABLE. ZROADZ cannot be held liable due to improper component installation and / or faulty wiring.

GENERAL GUIDELINES

LED Lights & LED Light Bars operate at relatively high currents and should only be installed by qualified personnel with experience in Switched / relayed high draw DC Circuits.

- Light Bars are designed for use only with standard 12v DC power systems
- Light Bars are for OFF-ROAD USE ONLY. Check your local laws & regulations regarding vehicle mounted lights.
- Some Light Bars are equipped with waterproof connectors while others are simply pig-tailed
- Red Wires = POSITIVE | Black Wires = NEGATIVE
- ALWAYS install your lights on a fused circuit. Basic fusing guidelines: maximum 5A for every 10" of LED Light Bar.

GENERAL USE, INSTALL AND ADJUSTMENT TIPS

NOTE 1: ZROADZ LED Light Bars themselves are for OFF-ROAD USE ONLY.

NOTE 2: Light Bars depending on the configuration of your vehicle and its options and/or modifications may need to be adjusted for appropriate beam projection. To adjust the angle of your light bars simply loosen the mounting hardware on either side of each Light Bar, rotate the Light Bar to adjust the angle, then tighten the hardware once the desired angle is achieved (please be careful not to over-tighten the mounting hardware or scratch the protective powder-coat finish). It is best to adjust the angle with the vehicle on level ground with the lights facing a wall, garage door or other solid barrier at a distance of approximately 25-30 feet.

NOTE 3: Please consult a qualified automotive electrical professional for light bar wiring installation.

NOTE 4: An optional universal wiring harness (part# Z390020S-A) is also available that includes high-heat & oil/fuel resistant wires, waterproof connector, 12v relay, 12v rocker switch, in-line fuse holder. Our universal wiring harness significantly expedites the installation process but is not a vehicles specific "Plug & Play" product and does not eliminate the need for a professional installation.

Please contact your local ZROADZ dealer for more information or visit www.zroadz.com.

PRODUCT CARE INFORMATION

PRODUCT CARE INFORMATION

Wash regularly as you would when caring for your vehicles. Never use dish soap. Never leave wet water spots as that may leave a blemish.

MATTE BLACK FINISH

Paint warranty applies to defects in material and / or workmanship, it does not cover the matte finish surface appearance.

To enjoy the matte appearance for many years to come, please follow these owner care and maintenance tips.

Get a no-shine matte car wash soap that uses no fillers, no silicone, and won't strip your matte paint of its layer of protection.

Do not use wax, detail spray, armorall®, or any products made for normal paint. Use only products specifically developed for matte finish paint. Do not use products that are even mildly abrasive, such as polishes, glazes, or rubbing compounds. Do not use mechanical cleaners or polishers. Do not use terry cloth, cloth, or paper towels. Do not rub the finish vigorously, this will burnish the paint finish, causing a permanent shiny spot. Shiny spots cannot be removed.

Do not use commercial car wash facilities or their shine enhancement products. Most car wash brushes, large mechanized "towels," and shine enhancement products can damage matte paint.

Remove foreign substances such as insect remains, tar, and road debris using a soft applicator and a mild solvent; saturate and soak area before cleaning—rub lightly.

Hand-wash with a soft wash mitt and mild cleaning product safe for matte paint. Use microfiber cleaning cloths with alcohol-based window cleaner for basic surface clean-up.

GLOSS BLACK FINISH

ZROADZ with Gloss Black Powder Coated Finish may be washed regularly as you would when caring for your vehicles finish using soap and water. ZROADZ should be waxed at the same time that you wax the vehicle. As a general rule, anything you use to clean your vehicles painted surfaces can be used to clean and maintain your ZROADZ grille. A Gloss powder Coated Finish can be cared for in the same fashion that you would care for your vehicles factory paint job. Never leave wet water spots as that may leave a blemish.

PARTS ARE PATENT PENDING. ALL RIGHTS RESERVED - COPYRIGHT ©2016 - ZROADZ LED, INC.